

Casquilho de agulhas

BA4410-ZOH-IKO - BA4410-ZOH-IKO

https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/ba4410-zoh-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BA...Z BHA...Z

Shaft dia.		Identification number							
mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Mass (Ref.) g
69.850 (2 3/4)	---	---	---	BA 4410 Z	85.5	---	---	---	---

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	q	Shaft dia. h7	Housing bore dia. J7	Max.	Min.	N	N	rpm	---
69.850 (2 3/4)	79.375 (3 1/8)	15.88 (.625)	2.8	69.850	69.831	79.393	79.383	25 000	50 800	3 500	---

Notes⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952049977
Diâmetro interior	69.85 mm
Diâmetro exterior	79.38 mm
Espessura	15.88 mm
Peso	88 g
Embalagem	-

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE