


Acessórios de mancal YAT205-100-SKF - YAT205-100-SKF

<https://www.123rolamento.pt/rolamento-mancal/mancal/aceessorios/yat205-100-skf>

Dimensions d'encrembrement			Charges de base		Vitesse limite	Désignation	
d	D	B	C	dynamique C	statique C ₀	avec tolérance d'arbre h6	
mm				kN		tr/min	
25,4	52	27,2	15	14	7,8	7000	- YAT 205-100



O₂ 1H.28 UNF
 C 15
 B₂ 5
 d₁ 33,7
 d 25,4
 B 27,2
 D 52
 r₁ 19,5
 r₂ 0,8
 O₁ 1H.28 UNF
 O₂ 1H.28 UNF
 O₃ 1H.28 UNF
 O₄ 1H.28 UNF
 O₅ 1H.28 UNF
 O₆ 1H.28 UNF
 O₇ 1H.28 UNF
 O₈ 1H.28 UNF
 O₉ 1H.28 UNF
 O₁₀ 1H.28 UNF
 O₁₁ 1H.28 UNF
 O₁₂ 1H.28 UNF
 O₁₃ 1H.28 UNF
 O₁₄ 1H.28 UNF
 O₁₅ 1H.28 UNF
 O₁₆ 1H.28 UNF
 O₁₇ 1H.28 UNF
 O₁₈ 1H.28 UNF
 O₁₉ 1H.28 UNF
 O₂₀ 1H.28 UNF
 O₂₁ 1H.28 UNF
 O₂₂ 1H.28 UNF
 O₂₃ 1H.28 UNF
 O₂₄ 1H.28 UNF
 O₂₅ 1H.28 UNF
 O₂₆ 1H.28 UNF
 O₂₇ 1H.28 UNF
 O₂₈ 1H.28 UNF
 O₂₉ 1H.28 UNF
 O₃₀ 1H.28 UNF
 O₃₁ 1H.28 UNF
 O₃₂ 1H.28 UNF
 O₃₃ 1H.28 UNF
 O₃₄ 1H.28 UNF
 O₃₅ 1H.28 UNF
 O₃₆ 1H.28 UNF
 O₃₇ 1H.28 UNF
 O₃₈ 1H.28 UNF
 O₃₉ 1H.28 UNF
 O₄₀ 1H.28 UNF
 O₄₁ 1H.28 UNF
 O₄₂ 1H.28 UNF
 O₄₃ 1H.28 UNF
 O₄₄ 1H.28 UNF
 O₄₅ 1H.28 UNF
 O₄₆ 1H.28 UNF
 O₄₇ 1H.28 UNF
 O₄₈ 1H.28 UNF
 O₄₉ 1H.28 UNF
 O₅₀ 1H.28 UNF
 O₅₁ 1H.28 UNF
 O₅₂ 1H.28 UNF
 O₅₃ 1H.28 UNF
 O₅₄ 1H.28 UNF
 O₅₅ 1H.28 UNF
 O₅₆ 1H.28 UNF
 O₅₇ 1H.28 UNF
 O₅₈ 1H.28 UNF
 O₅₉ 1H.28 UNF
 O₆₀ 1H.28 UNF
 O₆₁ 1H.28 UNF
 O₆₂ 1H.28 UNF
 O₆₃ 1H.28 UNF
 O₆₄ 1H.28 UNF
 O₆₅ 1H.28 UNF
 O₆₆ 1H.28 UNF
 O₆₇ 1H.28 UNF
 O₆₈ 1H.28 UNF
 O₆₉ 1H.28 UNF
 O₇₀ 1H.28 UNF
 O₇₁ 1H.28 UNF
 O₇₂ 1H.28 UNF
 O₇₃ 1H.28 UNF
 O₇₄ 1H.28 UNF
 O₇₅ 1H.28 UNF
 O₇₆ 1H.28 UNF
 O₇₇ 1H.28 UNF
 O₇₈ 1H.28 UNF
 O₇₉ 1H.28 UNF
 O₈₀ 1H.28 UNF
 O₈₁ 1H.28 UNF
 O₈₂ 1H.28 UNF
 O₈₃ 1H.28 UNF
 O₈₄ 1H.28 UNF
 O₈₅ 1H.28 UNF
 O₈₆ 1H.28 UNF
 O₈₇ 1H.28 UNF
 O₈₈ 1H.28 UNF
 O₈₉ 1H.28 UNF
 O₉₀ 1H.28 UNF
 O₉₁ 1H.28 UNF
 O₉₂ 1H.28 UNF
 O₉₃ 1H.28 UNF
 O₉₄ 1H.28 UNF
 O₉₅ 1H.28 UNF
 O₉₆ 1H.28 UNF
 O₉₇ 1H.28 UNF
 O₉₈ 1H.28 UNF
 O₉₉ 1H.28 UNF
 O₁₀₀ 1H.28 UNF

O₁ hexagonal (mm)
 2175
 Couple de serrage recommandé (Nm)
 4
 Graisse caoutchouc appropriée
 RS 205
 Coefficient de calcul
 f₀ 14

CARACTERÍSTICAS DO PRODUTO

Marca	SKF
Nº Ean13	7316571504582
Diâmetro interior	25.4 mm
Diâmetro exterior	52 mm
Espessura	27.2 mm
Aperto	-
Peso	170 g
Embalagem	-

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE