

## Rolamento de rolos NCF2956CV-SKF - NCF2956CV-SKF

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/ncf2956cv-skf>

Dimensions d'encombement			Charges de base		Vitesse de base		Designation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
280	380	60	880	1730	700	800	NCF 2956 CV

  

Technical drawing showing dimensions and coefficients for the NCF2956CV roller bearing. The drawing includes a cross-section of the bearing with dimensions: d = 280 mm, D = 380 mm, B = 60 mm, r\_max = 2.1 mm, r\_min = 2.1 mm, E = 295.3 mm, E<sub>2</sub> = 247.5 mm, d<sub>2</sub> = 314 mm, S = 60 mm, r<sub>2</sub> = 3.5 mm. It also shows a detail of the outer ring with dimensions: D<sub>max</sub> = 369 mm, D<sub>min</sub> = 369 mm, r<sub>max</sub> = 2 mm, r<sub>min</sub> = 2 mm, D<sub>max</sub> = 369 mm, D<sub>min</sub> = 369 mm, r<sub>max</sub> = 2 mm, r<sub>min</sub> = 2 mm. Coefficients of calculation are listed as k<sub>r</sub> = 0.2, k<sub>a</sub> = 0.3, and Y = 0.4.

### CARACTERÍSTICAS DO PRODUTO

Marca	SKF
Nº Ean13	7316572412930
Diâmetro interior	280 mm
Diâmetro exterior	380 mm
Espessura	60 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE