


Rolamento de agulhas NART5-VR-IKO - NART5-VR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nart5-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers Full Complement Type/With Inner Ring



| Shaft dia. mm | Shield type Crowned outer ring | | | | Identification number | | Sealed type Crowned outer ring | | Mass (Ref.) |
|------------------------|-----------------------------------|-----------------|-----------|-----------------|---|---|------------------------------------|-----------------|----------------|
| | With cage | Full complement | With cage | Full complement | With cage | Full complement | With cage | Full complement | |
| 5 | — | NART 5 VR | — | — | — | — | — | — | 15.1 |
| Boundary dimensions mm | | | | | | | | | |
| <i>d</i> | <i>D</i> | <i>B</i> | <i>C</i> | <i>a</i> | Basic static load rating <i>C</i> N | Basic dynamic load rating <i>C</i> ₀ N | Maximum allowable static load N | | |
| 5 | 16 | 12 | 11 | 12 | 6 810 | 8 370 | 7 310 | | |

Remarks: 1. The inner ring has an oil hole.
2. The sealed type is provided with prepacked grease. The shield type is not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952303628 |
| Diâmetro interior | 5 mm |
| Diâmetro exterior | 16 mm |
| Espessura | 12 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE