


Rolamento de agulhas CRY20-V-IKO - CRY20-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/cry20-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series Full Complement Type /With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)			
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C
9.525 (3/8)	CRY 20 V		109	9.525 $\frac{3}{8}$	31.750 (1 1/4)	20.639(0.8125)	19.050 $\frac{3}{4}$
		Shaft dia.			Basic dynamic load rating C		Basic static load rating C ₀
		Push fit		Drive fit		Press fit	
		Min.	Max.	Min.	Max.	Min.	Max.
25.00(984)	1.588 (1/4)	9.507	9.517	9.523	9.533	9.528	9.538
						23 600	31 700

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952304175
Diâmetro interior	9.53 mm
Diâmetro exterior	31.75 mm
Espessura	20.64 mm
Peso	103 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE