


Rolamento cónico 26112-26274-TIMKEN - 26112-26274-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/26112-26274-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 28.575 | 69.722 | 19.050 | 6900 | 1.67 | 19100 | 11900 | 1.62 | 69300 | 26112 26274 | |
| 1.1290 | 2.7450 | 0.7500 | 15700 | | 4600 | 2500 | | 15500 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | | |
|--------------------|--------|--------------------------|------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|--------|------|
| Width B | | ER. Dr. e ⁽¹⁾ | | Shaft | | Housing | | Cage | | G ₁ | G ₂ | C ₃ | | | |
| mm | mm | mm | mm | Max Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | kg | | |
| 19.053 | 19.050 | -0.1 | 0.06 | 1.5 | 35.8 | 37.8 | 1.5 | 64.9 | 61.8 | 8.5 | 11.1 | 16.1 | 10.1 | 0.9030 | 0.87 |
| 0.7490 | 0.7500 | -0.16 | 0.06 | 1.28 | 1.46 | 0.06 | 2.96 | 2.40 | 0.02 | 0.05 | | | | | |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952308746 |
| Diâmetro interior | 28.58 mm |
| Diâmetro exterior | 69.72 mm |
| Espessura | 19.05 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE