

Rolamento cónico 2788-2734-TIMKEN - 2788-2734-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/2788-2734-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|-------------|-------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | |
| 38.100 | 79.375 | 25.400 | 8000 | 0.01 | 2200 | 1.52 | 16200 | 2788 | 2734 |
| 1.500 | 3.125 | 1.000 | 1950 | | 560 | 203 | 2300 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|--------|------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Width | | ER. Co. μm | Shaft | | Housing | | Cage | | G ₁ | G ₂ | C ₃ | | | |
| mm | mm | | Max Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ₁ | Backing Shoulder Dia. D _s | A ₁ ⁽⁵⁾ | A ₂ ⁽⁶⁾ | | | | | | |
| 25.404 | 25.408 | -0.1 | 0.5 | 43.5 | 58.8 | 3.3 | 32.0 | 62.8 | 1.4 | 8.9 | 20.7 | 12.2 | 0.025 | 8.58 |
| 1.010 | 0.9125 | -0.32 | 0.14 | 1.71 | 1.97 | 0.13 | 2.83 | 2.64 | 0.05 | 0.04 | | | | 1.28 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952311890 |
| Diâmetro interior | 38.1 mm |
| Diâmetro interior | 1 1/2" inch |
| Diâmetro exterior | 79.375 mm |
| Diâmetro exterior | 3 1/8" inch |
| Espessura | 25.4 mm |
| Espessura | 1" inch |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE